## **GENERAL CONSTRUCTION NOTES**

- 1. ALL WORK DETAILED ON THESE PLANS SHALL BE CONSTRUCTED TO THE SATISFACTION OF THE CITY ENGINEER IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (LATEST EDITION) INCLUDING ALL AMENDMENTS ADOPTED THERETO PRIOR TO THE DATE OF APPROVAL OF THESE PLANS AND IN ACCORDANCE WITH THE STANDARD DRAWINGS OF THE CITY OF WEST COVINA UNLESS OTHERWISE SPECIFIED.
- 2. THE DESIGN ENGINEER \_\_\_\_\_\_\_HAS INVESTIGATED THE RECORDS OF THE CITY AND THE MAPS, WHICH THE UTILITY COMPANIES HAVE FILED WITH THE CITY, AND HAS NOTIFIED ALL UTILITY COMPANIES. UTILITY FACILITIES WILL BE MARKED IN THE FIELD PRIOR TO START OF CONSTRUCTION.
- 3. BEFORE WORK COMMENCES, THE CONTRACTOR MUST OBTAIN A PERMIT TO EXCAVATE IN THE CITY STREETS FROM THE BUILDING AND ENGINEERING DEPARTMENT.
- 4. THE CONTRACTOR SHALL COMPLY WITH THE REQUIREMENTS FOR TRAFFIC CONTROL AS OUTLINED IN THE LATES EDITION OF "WORK AREA TRAFFIC CONTROL HANDBOOK" PUBLISHED BY BUILDING NEWS, INC.
- 5. JOINTS IN ALL CONCRETE WORK SHALL CONFORM TO THE PROVISIONS IN SECTION 303-5.4 OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORK CONSTRUCTION, LATEST EDITION, AND AS DIRECTED BY THE CITY INSPECTOR.
- 6. THE FINISHED SURFACE OF THE ROADWAY SHALL CONFORM TO A UNIFORM TRANSITION BETWEEN SECTIONS SHOWN HERE ON AND SECTIONS IN PLACE WHERE NECESSARY, THE CONTRACTOR SHALL REMOVE A PORTION OF EXISTING PACEMENT AND RESURFACE TO PROVIDE A SMOOTH JOIN.
- 7. CRUSHED AGGREGATE BASE SHALL CONFORM TO THE GRADATION OF SECTION 200-2.2.2 OF THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION.
- ALL ASPHALTIC CONCRETE PAVEMENT SHALL BE TYPE PG 64-10 AND SHALL BE APPLIED IN TWO LAYERS. BASE COURSE SHALL BE B PG 64-10, AND SURFACE COURSE SHALL BE C2-PG 64-10.
- 9. THE CONTRACTOR AND THE CITY INSPECTOR SHALL VISIT ALL LOCATIONS PRIOR TO THE COMMENCEMENT OF THE WORK.

- 10. ALL SURROUNDING STREETS AND DISTURVED AREAS SHALL BE SWEPT AND KEPT CLEAN BY THE END OF EACH WORKING DAY OR AS OTHERWISE DIRECTED BY THE CITY INSPECTOR.
- 11. THE CONTRACTOR SHALL MAINTAIN DUST CONTROL. DUST SHALL BE KEPT TO A MINIMUM AS DIRECTED BY THE CITY INSPECTOR.
- 12. WORKING HOURS ON SITE SHALL BE FROM 8:00 AM TO 5:00 PM UNLESS OTHERWISE SPECIFIED BY THE CITY INSPECTOR.